

**MT72-3VI****Reciprocating compressor, MT72HN3CVE**

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

**PRODUCT DETAILS**

<b>Gross weight</b>	44.5 Kg
<b>Net weight</b>	42 Kg
<b>Volume</b>	61.54 Liter
<b>EAN</b>	5702428839556
<b>Approval</b>	CE UL UKCA
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>China RoHS compliance</b>	Out of scope
<b>Colour</b>	Blue
<b>Compressor power supply [V]</b>	200-230/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT072-3
<b>Diameter [mm]</b>	288 mm
<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Family</b>	MT
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF
<b>Fitting standard</b>	Rotolock
<b>Frequency [Hz]</b>	60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>GP LP torque [Nm]</b>	15 N-m
<b>High Side TS Max</b>	150 °C
<b>High Side TS Min</b>	-35 °C

## Product Detail | Reciprocating compressor, MT72HN3CVE

## PRODUCT DETAILS

High Side Volume	0.6 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 60Hz [V]	200 V
Low value of voltage range at 60Hz [V]	180 V
LRA	135 A
Max pressure (PS) - high side	27.8 bar
Max pressure (PS) - low side	18.4 bar
MCC	30 A
Model number	MT72HN3CVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	41 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	MT
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R22
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Reciprocating compressor, MT72HN3CVE**
**PRODUCT DETAILS**

<b>Suction connection pipe size [in]</b>	7/8 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Swept volume [cm<sup>3</sup>]</b>	120.94 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Test Dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT072
<b>UK RoHS compliance</b>	Out of scope
<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	0.56 Ohm
<b>Proposition 65</b>	WARNING: Cancer and Reproductive Harm <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

**Accessories**

**120Z0763** [🔗](#)
**Mounting, Compressor kit**

Mounting kit 2 cylinder


**120Z0576** [🔗](#)
**Acoustic hood, Reciprocating**

Acoustic hood for two-cylinder compressor


**8153013** [🔗](#)
**Connector, Solder Sleeve**

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)


**8156134** [🔗](#)
**Electrical component, Terminal box**

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp


**8156009** [🔗](#)
**Connector, GASKET**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Reciprocating compressor, MT72HN3CVE

## Accessories

**8156131** [🔗](#)**Connector, GASKET**

Gasket, 1-1/4"

**8153008** [🔗](#)**Connector, Solder Sleeve**

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

**8156132** [🔗](#)**Connector, GASKET**

Gasket, 1-3/4"

## Spare Parts

**7754001** [🔗](#)**Lubricant, 160P**

Mineral oil, 160P, 2-litre can

**7703006** [🔗](#)**Connector, Valve set**

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")

**8156145** [🔗](#)**Connector, GASKET**

Gasket for oil sight glass (black chloroprene)

**8168032** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)

**7773107** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 230 V, CE mark, UL

**7773109** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 110 V, CE mark, UL

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



**120Z0459** [↗](#)

**Crankcase heater, PTC heater**

PTC heater 27W, CE mark, UL



**8156019** [↗](#)

**Connector, Sight glass**

Oil sight glass with gaskets (black and white)



**8168029** [↗](#)

**Connector, Rotolock service valve**

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.